

SAFETY DATA SHEET

STIKATAK 300

Page: 1

Compilation date: 06/02/2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: STIKATAK 300

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Interfloor Ltd
Broadway
Haslingden
Rossendale
Lancashire
BB4 4LS
United Kingdom

Tel: 01706 213131

Fax: 01706 224915

Email: chris.mcgilvray@interfloor.com

1.4. Emergency telephone number

Emergency tel: 01706 213131

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Skin Sens. 1A: H317; Eye Irrit. 2: H319; -: EUH208

Most important adverse effects: Contains biocide b, 65. May produce an allergic reaction. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains biocide b, 65. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark

SAFETY DATA SHEET

STIKATAK 300

Page: 2



Signal words: Warning

Precautionary statements: P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.
P264: Wash hands thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+352: IF ON SKIN: Wash with plenty of water/.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321: Specific treatment (see instructions on this label).

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

CALCIUM CARBONATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	1317-65-3	Substance with a Community workplace exposure limit.	-	10-30%

POLYMERIC AQUEOUS DISPERSION (L)

-	-	Substance with a Community workplace exposure limit.	-	10-30%
---	---	--	---	--------

WHITE SPIRIT

-	-	-	Flam. Liq. 3: H226; Aquatic Chronic 3: H412; Skin Irrit. 2: H315; Asp. Tox. 1: H304	1-10%
---	---	---	---	-------

VULCANISATION AGENT

-	-	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1A: H317; Aquatic Chronic 2: H411; Aquatic Acute 1: H400	<1%
---	---	---	--	-----

BIOCIDE BASED ON 1,2 BENZISOTHIAZOL-3(2H)-ONE AND 2 METHYLLISOTHIAZOL-3(2H)-ONE

-	-	-	Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Sens. 1: H317	<1%
---	---	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

[cont...]

SAFETY DATA SHEET

STIKATAK 300

Page: 3

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

[cont...]

SAFETY DATA SHEET

STIKATAK 300

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

CALCIUM CARBONATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	10mg/m3	-	-	-

POLYMERIC AQUEOUS DISPERSION (L)

UK	2.5mg/m3	2.5mg/m3	-	-
----	----------	----------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Solid

Colour: Off-white

Odour: Barely perceptible odour

Evaporation rate: Slow

Oxidising: Not applicable.

Solubility in water: Soluble

[cont...]

SAFETY DATA SHEET

STIKATAK 300

Page: 5

Viscosity: Not applicable.

Boiling point/range°C: >35

Flammability limits %: lower: Not applicable.

Flash point°C: >93

Autoflammability°C: Not applicable.

Relative density: Not applicable.

VOC g/l: Not applicable.

Melting point/range°C: Not applicable.

upper: Not applicable.

Part.coeff. n-octanol/water: Not applicable.

Vapour pressure: Not applicable.

pH: Approx. 7

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

WHITE SPIRIT

DERMAL	RBT	-	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

VULCANISATION AGENT

DERMAL	RBT	LD50	>7940	mg/kg
--------	-----	------	-------	-------

[cont...]

SAFETY DATA SHEET

STIKATAK 300

Page: 6

ORAL	RAT	LD50	7500	mg/kg
------	-----	------	------	-------

BIOCIDE BASED ON 1,2 BENZISOTHIAZOL-3(2H)-ONE AND 2 METHYLLISOTHIAZOL-3(2H)-ONE

DERMAL	RAT	LD50	>2000	mg/kg
DUST/MIST	RAT	LD50	5.71	mg/l
ORAL	RAT	LD50	>2500	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

WHITE SPIRIT

ALGAE	48H EC50	10<>100	mg/l
FISH	48H EC50	10<>100	mg/l

VULCANISATION AGENT

Daphnia magna	48H EC50	4.1	mg/l
---------------	----------	-----	------

BIOCIDE BASED ON 1,2 BENZISOTHIAZOL-3(2H)-ONE AND 2 METHYLLISOTHIAZOL-3(2H)-ONE

Daphnia magna	48H EC50	32	mg/l
---------------	----------	----	------

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

[cont...]

SAFETY DATA SHEET

STIKATAK 300

Page: 7

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2811

14.2. UN proper shipping name

Shipping name: TOXIC SOLID, ORGANIC, N.O.S.

14.3. Transport hazard class(es)

Transport class: 6.1

14.4. Packing group

Packing group: I

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: C/E

Transport category: 1

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

SAFETY DATA SHEET

STIKATAK 300

Page: 8

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.