

interfloor

SAFETY DATA SHEET

STIKATAK Gripper Adhesive



Interfloor Limited

Broadway, Haslingden, Rossendale, Lancashire, BB4 4LS United Kingdom

Enquiries

Tel: +44 (0)1706 238810

sales@interfloor.com

interfloor.com

Product	STIKATAK GRIPPER ADHESIVE S7512	Page	1 of 7	Version #	1
		Date	02/03/2023	SDS #	100012

Section 1: Identification

Product Name: STIKATAK GRIPPER ADHESIVE S7512

Chemical Name/Synonyms: STIKGRIPC3

Company:

INTERFLOOR LTD

Broadway, Haslingden,
Rossendale, Lancashire,
BB4 4LS, UK.

Tel: 01706 213131

Fax: 01706 260800

Email: technical@interfloor.com

Section 2: Hazard(s) Identification

2.1 Classification of the substance or mixture

Classification (EC1272/2008)

Aquatic Chronic 3: H412;

Eye Irrit. 2: H319;

Flam. Liq. 2: H225;

Skin Irrit. 2: H315;

STOT SE 3: H336 –

Most important adverse effects: Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

- Hazard pictograms



GHS07



GHS07

- Signal word **Danger**

- Hazard statements

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Product	STIKATAC GRIPPER ADHESIVE S7512	Page	2 of 7	Version #	1
		Date	02/03/2023	SDS #	100012

- Precautionary statements

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical equipment.

P280: Wear protective gloves / eye protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair):

Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/ Information on Ingredients

Mixtures

Description: Mixture

ETHYL ACETATE - REACH registered number(s): 01-2119475103-46-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
205-500-4	141-78-6	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%

NAPHTHA (PETROLEUM) HYDROTREATED LIGHT - REACH registered number(s): 01-2119475514-35-XXXX

265-151-9	64742-49-0	-	Flam. Liq. 2: H225; Aquatic Chronic 2: H411; Skin Irrit. 2: H315; STOT SE 3: H336; Asp. Tox. 1: H304	1-10%
-----------	------------	---	--	-------

NAPHTHA (PETROLEUM), SOLVENT-REFINED LIGHT - REACH registered number(s): 01-2119473851-33-XXXX

920-750-0	-	-	Flam. Liq. 2: H225; Aquatic Chronic 2: H411; Skin Irrit. 2: H315; STOT SE 3: H336; Asp. Tox. 1: H304	1-10%
-----------	---	---	--	-------

Section 4: First-Aid Measures

4.1 Description of first aid measures

Note Personal protective equipment for first aid responders is recommended.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

Skin Contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye Contact: Rinse opened eye for several minutes under running water. Then consult doctor.

Ingestion: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Eye bathing equipment should be available on the premises.

Product	STIKATAC GRIPPER ADHESIVE S7512	Page	3 of 7	Version #	1
		Date	02/03/2023	SDS #	100012

Section 5: Fire-Fighting Measures

5.1 Extinguishing media

Water spray

Alcohol-resistant foam Fire-extinguishing powder Carbon dioxide, Water Spray

Use water spray to cool containers.

5.2 Special hazards arising from the substance or media

Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3 Advice for firefighters

Protective equipment: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes..

Section 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Eliminate all sources of ignition.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

Section 7: Handling and Storage

7.1 Precautions for safe handling Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

- 7.2 Conditions for safe storage, including any incompatibilities

- Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition.

Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

- 7.3 Specific end use(s) No further relevant information available.

Section 8: Exposure Controls/Personal Protection

8.1 Control parameters

Hazardous ingredients:

ETHYL ACETATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	200 ppm	400 ppm	-	-

NAPHTHA (PETROLEUM) HYDROTREATED LIGHT

EU	1200ppm	-	-	-
----	---------	---	---	---

Product	STIKATAC GRIPPER ADHESIVE S7512	Page	4 of 7	Version #	1
		Date	02/03/2023	SDS #	100012

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED LIGHT

Type	Exposure	Value	Population	Effect
DNEL	Dermal	300 mg/kg	Workers	Systemic
DNEL	Inhalation	2085 mg/m3	Workers	Systemic
DNEL	Oral	149 mg/kg bw/day	Consumers	Systemic

8.2 Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

State: Liquid

Colour: Beige

Odour: PETROL-LIKE

Evaporation rate: Fast

Solubility in water: Insoluble

Viscosity: Highly viscous

Boiling point/range°C: >35

Flash point°C: <23

Relative density: ~1.3

VOC g/l: 373

9.2 Other Information: No data available

Section 10 Stability and reactivity

- **10.1 Reactivity** Stable under normal storage conditions.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
- **10.5 Incompatible materials:** Strong oxidising agents. Strong acids.
- **10.6 Hazardous decomposition products:** In combustion emits toxic fumes.

Product	STIKATAC GRIPPER ADHESIVE S7512	Page	5 of 7	Version #	1
		Date	02/03/2023	SDS #	100012

Section 11: Toxicological Information

11.1 Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
IHL	RAT	LC50	-	-
SKN	-	-	-	-

Hazardous ingredients:

ETHYL ACETATE

DERMAL	RBT	LD50	>20000	mg/kg
ORAL	RAT	LD50	6100	mg/kg
ORAL	RBT	LD50	4934	mg/kg
VAPOURS	RAT	4H LC50	29.3	ppmV

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms/routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological Information

12.1 Toxicity

ETHYL ACETATE

Daphnia magna	48H EC50	3090	mg/l
Pimephales promelas (Fat-head Minnow)	96H LC50	230	mg/l

12.2 Persistence and degradability:

Biodegradable

12.3 Bioaccumulative potential:

No bioaccumulation potential

12.4 Mobility:

Readily absorbed into soil.

12.5 PBT identification:

This product is not identified as a PBT/vPvB substance.

12.6 Other adverse effects:

Negligible ecotoxicity.

Product	STIKATAC GRIPPER ADHESIVE S7512	Page	6 of 7	Version #	1
		Date	02/03/2023	SDS #	100012

Section 13: Disposal Considerations

13.1 Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport Information

UN number: UN1133

Shipping name: ADHESIVES (ETHYL ACETATE; NAPHTHA (PETROLEUM) HYDROTREATED LIGHT)

Transport class: 3

Packing group: III

Environmentally hazardous: No

Marine pollutant: No

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
N/A

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

Section 16: Other Information

Whilst the company has taken every care in the preparation of these particulars, no liability is attached for any loss or damage arising from reliance upon information which has been prepared specifically for the purposes of the Control of Substance Hazardous to Health Regulations 2002. The details of composition of products are given entirely for the purposes of the Regulations and, as the composition may vary from time to time, are not given as warranty of specification of products of their use.

Data is given for guidance only and does not form part of any specification.

This material should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulations.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process.

It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

Product	STIKATAC GRIPPER ADHESIVE S7512	Page	7 of 7	Version #	1
		Date	02/03/2023	SDS #	100012

For commercial use only.

- **Legend of H- and R-phrases, concerning the in chapter 3 mentioned substances (marking of product please see chapter 2)**

EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

SDS date of preparation/update: 02/03/2023